DAMPER PART NUMBERS

Gas and automatic solid fuel dampers. Every damper uses the same 4-pin Molex. Choose the damper by fuel, then pair it with a controller for that fuel.

GAS, TOP-MOUNT

Controllers: XV-GBC, XV-GBC-DUO, Meridian (XV-MERD-CTRL), Meridian DUO (XV-MERD-DUO). **Stand-alone:** XV-GFDC.

PART NUMBER	FLUE SIZE	DRAFT INDUCER
XV-GFD250-8	8"	XV150, XV250
XV-GFD250-10	10"	XV150, XV250
XV-GFD250-12	12"	XV250
XV-TMD1250-13	13"	XV150, XV250
XV-GFD250-14	14"	XV250
XV-GFD350-12	12"	XV350
XV-TMD350-13	13"	XV350
XV-GFD350-14	14"	XV350
XV-GFD350-16	16"	XV350

GAS, INLINE

Controllers: XV-GBC, XV-GBC-DUO, Meridian (XV-MERD-CTRL), Meridian DUO (XV-MERD-DUO). **Stand-alone:** XV-GFDC.

PART NUMBER	FLUE SIZE	DRAFT INDUCER
XV-INLD-8	8"	Any, or none
XV-INLD-10	10"	Any, or none
XV-INLD-12	12"	Any, or none
XV-INLD-13	13"	Any, or none
XV-INLD-14	14"	Any, or none
XV-INLD-16	16"	Any, or none

AUTOMATIC SOLID FUEL, TOP-MOUNT

Controllers: XV-WBC, XV-WBC-DUO. **Stand-alone:** XV-SFDC.

PART NUMBER	FLUE SIZE	DRAFT INDUCER
XV-SFD1250-8	8"	XV150, XV250
XV-SFD1250-10	10"	XV150, XV250
XV-SFD1250-12	12"	XV150, XV250
XV-SFD1250-13	13"	XV150, XV250
XV-SFD1250-14	14"	XV150, XV250
XV-SFD1250-16	16"	XV150, XV250
XV-SFD1250-DM	DM54 flue	XV150, XV250
XV-SFD350-12	12"	XV350
XV-SFD350-13	13"	XV350
XV-SFD350-14	14"	XV350
XV-SFD350-16	16"	XV350
XV-SFD350-DM	DM54 flue	XV350

Top-mount dampers carry the draft inducer, so they are selected by draft inducer model and flue size: 350 in the part number fits the XV350; 250 and 1250 fit the XV250, and the sizes listed with XV150 fit it too. Inline dampers install in the flue run, so they are selected by flue size alone. All dampers are listed to UL 378 (ETL Listed, Intertek control no. 4007025). Gas dampers are listed for gas appliances only, seal the flue when closed, and fail closed on power loss. The solid fuel damper has no seal by design and fails open. Questions: 800.642.2920.